



TURN
WORKSPACES
INTO
SAFE PLACES

INTRODUCING PRO-TACT BALLISTIC BARRIERS

- Panels designed to integrate discreetly into any environment while providing added safety benefits and security for any lobby area, check point or workspace.
- Panels, in both the stationary and mobile models, and all joint connections in the stationary model have been UL 752 Level 7 and 8 certified and independently tested to NIJ Level 3. For certain ballistic materials, UL 7 poses a greater threat than either UL 8 or NIJ3; as a result, Claridge designed Pro-Tact Barriers to achieve dual UL certifications.
- Panels are bi-directional and contain a high hardness steel core coated with 100% polyurea elastomer to lessen ricochet, spall and splatter.
- Panels meet ASTM E-84 Class A and have been GREENGUARD certified for indoor air quality.



STATIONARY BALLISTIC PANELS

- Satin anodized aluminum framed barriers are UL 752 Level 7 and 8 certified and NIJ Level 3 tested
- Standard heights and widths range from 4' (H) x 2' (W) to 6' (H) x 4' (W)
- Select height, then mix and match widths and joint connections to fit coverage area
- Specify type of joint configuration connection desired when ordering more than one panel
- Panels can be joined in 45-degree, 90-degree or in-line (straight) configurations
- Finished surface options include Porcelain enamel steel markerboard or Designer Series Fabric tackable surfaces in your choice of 10 colors

MOBILE BALLISTIC DISPLAYS

- Satin anodized aluminum framed mobile barriers are UL 752 Level 7 and 8 certified and NIJ Level 3 tested
- Standard heights and widths range from 4' (H) x 3' (W) to 6' (H) x 4' (W)
- Heavy-duty casters allow mobile to be easily repositioned
- Finished surface options include Porcelain enamel steel markerboard or Designer Series Fabric tackable surfaces in your choice of 10 colors



Ordering Panels

- When ordering multiple stationary panels, select height and then mix and match panel widths and joint connections to fit the coverage area desired.
- Non-standard width panels can be ordered with pricing equal to the next larger standard width panel.
- Non-standard height panels can be ordered with pricing equal to the next larger standard height panel.
- Specify either tackable fabric or porcelain enamel writing surface. If tackable surface, specify fabric color from our Designer Series Fabric selection.

Contact us at 800.434.4610 or visit our website at www.claridgeballisticbarriers.com.



PRO-TACT[®]
BALLISTIC BARRIERS by Claridge

