

## TrakIt Installation Instructions

1. Determine position on wall. Using a level, measure up required distance from the floor, and strike a line. Position track so that bottom edge is on line, marking center of mounting slots.

Note: If ceiling and/or floor is not completely level, track may need to be adjusted slightly.

2. If necessary, cut aluminum track and plastic cover to length.
3. Drill ½” holes in wall at marks. Install your toggle bolts, or preferred fasteners, through track and into wall.
4. Making sure toggle is open completely, tighten as track is pulled out to keep toggle bolt from spinning.

If track is to be installed end-to-end, proceed to end-to-end installation instructions below.

5. Install plastic end caps in each end and fasten with Phillips head screw before snapping plastic cover into place.
6. Position plastic cover onto track and snap into position.

### **For end-to-end track installations, we suggest the following:**

Install end caps on outside ends of track.

Note: For optimum performance, stagger aluminum track seams and plastic cover plate seams.

When installing the plastic cover, overlap the track seam with the cover. (For example: Two 6’ sections of track are installed on the wall. Using one 6’ piece and two 3’ pieces, install a 3’ section first, then the 6’ section, finishing with the 3’.)

CLARIDGE PRODUCTS AND EQUIPMENT, INC.

P. O. BOX 910

HARRISON, AR 72602-0910

PHONE: 870-743-2200

FAX: 870-743-1908

[www.connectbyclaridge.com](http://www.connectbyclaridge.com)

